McCormick MTX Series Tractors

MTX

120-135-150 (T3)

McCORMICK™

		MTX 120 (T3)	MTX 135 (T3)	MTX 150 (T3)
ENGINE				
TIER 3		BETAPOWER	BETAPOWER	BETAPOWER
MAXIMUM POWER ISO	HP/KW	117/86	133/98	141/104
NO. OF CYLINDERS/TURBO/WASTEGATE/INTERCOOLER		6 / T / W / I	6 / T / W / I	6 / T / W / I
DISPLACEMENT	IN (CM^3)	6.728	6.728	6.728
BORE/STROKE	IN (MM)	4/5 (104/132)	4/5 (104/132)	4/5 (104/132)
MAXIMUM GROSS TORQUE	FT/LB (NM)	379 (515)	412 (559)	435 (625)
MAXIMUM RATED SPEED	RPM	1250	1250	1250
TORQUE RISE %		40	39	39
FUEL TANK CAPACITY	GAL (LITRES)	70 (265)	70 (265)	70 (265)
TRANSMISSION				
BASE TRANSMISSION + POWER SHUTTLE (4 POWERSHIFT SPEEDS)		16AV + 12RM	16AV + 12RM	16AV + 12RM
BASE TRANSMISSION + CREEPER + POWER SHUTTLE		32AV + 24RM	32AV + 24RM	32AV + 24RM
AUTOSPEED + POWER SHUTTLE (4 POWERSHIFT SPEEDS)		16AV + 13RM	16AV + 13RM	16AV + 13RM
HYDRAULIC POWER SHUTTLE		●	●	●
ELECTROHYDRAULIC REAR DIFF-LOCK		●	●	●
POWER TAKE-OFF				
NET PTO POWER (ISO RATING)	HP/KW	100/ 73	114/ 84	117/ 86
MULTI-DISC WET CLUTCH		●	●	●
ELECTROHYDRAULIC ENGAGEMENT		●	●	●
SPEEDS 540/1000 RPM		●	●	●
FRONT AXLE				
FIXED TYPE		●	●	●
TYPE WITH HYDRAULIC SUSPENSIONS		○	○	○
ELECTROHYDRAULIC 4 WD ENGAGEMENT		●	●	●
LIMITED SLIP DIFFERENTIAL		●	●	●
STEERING ANGLE		55°	55°	55°
MINIMUM TURNING RADIUS	IN (MM)	183 (4.650)	183 (4.650)	183 (4.650)
BRAKES				
REAR WET DISC GRAPHITE BRAKES		●	●	●
AUTOMATIC 4WD ENGAGEMENT ON BRAKING		●	●	●
PNEUMATIC BRAKING		○	○	○
HYDRAULIC POWER LIFT				
ELECTRONICALLY OPERATED		●	●	●
MAXIMUM LIFT CAPACITY	LBS (KG)	12,943/14,555 (5871/6602)	12,943/14,555 (5871/6602)	12,943/14,555 (5871/6602)
MAXIMUM PUMP FLOW	GAL (L)/MIN	29 (109)	29 (109)	29 (109)
CATEGORY		CAT. IIIN	CAT. IIIN	CAT. IIIN
AUXILIARY VALVES STD		3	3	3
FRONT HITCH AND PTO	(LIFT CAPACITY KG) KG	3500 ○	3500 ○	3500 ○
CAB AND DRIVING POSITION				
"DELUXE" CAB / AUTO-RADIO FITTING FACILITIES		●	●	●
HEATING / VENTILATION		●	●	●
AIR-CONDITIONING		●	●	●
PNEUMATIC SEAT		○	○	○
DIMENSIONS AND WEIGHTS				
FRONT TIRES		420/85R28	420/85R28	420/85R28
REAR TIRES		520/85R38	520/85R38	520/85R38
OVERALL LENGTH (REAR LINKS - FRONT WEIGHTS)	IN (MM)	203 (5160)	203 (5160)	203 (5160)
WHEELBASE	IN (MM)	107 (2723)	107 (2723)	107 (2723)
OVERALL WIDTH ACROSS REAR FENDERS	IN (MM)	90 (2300)	90 (2300)	90 (2300)
HEIGHT OVER DELUXE CAB	IN (MM)	114 (2910)	114 (2910)	114 (2910)
GROUND CLEARANCE	IN (MM)	20 (505)	20 (505)	20 (505)
MIN. SHIPPING WEIGHT	LBS (KG)	11,905 (5400)	11,905 (5450)	11,905 (5400)
OPTIONAL EQUIPMENT				
10 FRONT WEIGHTS OF 45 KG		○	○	○
HYDRAULIC TRAILER BRAKING		○	○	○
PNEUMATIC TRAILER BRAKING		○	○	○

Key: ● standard ○ option — not available

(GB) All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.
progetto grafico: **gruppo saldatori** bzzbzz@grupposaldatori.com

McCormick International USA, Inc.
2590 Breckinridge Blvd. • Duluth, GA 30096
866.327.6733 • www.McCormickUSA.com

McCormick and McCormick Logo are registered trademarks of McCormick International USA in the U.S. and/ or other countries. International Harvester and Farmall are trademarks of CNH America LLC. © 2012 McCormick International USA, Inc. All Rights Reserved. This literature has been published for world-wide circulation. The standard and optional equipment and the availability of individual models might vary from one country to the next. McCormick International USA, Inc. reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. While every effort is made to ensure that the specifications, descriptions, and illustrations in this brochure are correct at the time of printing, these are also subject to change without prior notice. Illustrations might show optional equipment, and might not show all standard equipment.

McCORMICK™